

PERFORMANCE CURVE FOR CULVERT 1 - One (2100 mm BY 1200 mm) RCB

DIS- CHARGE FLOW (m ³ /s)	HEAD- WATER ELEV. (m)	INLET CONTROL DEPTH (m)	OUTLET CONTROL DEPTH (m)	FLOW TYPE <F4>	NORMAL DEPTH (m)	CRIT. DEPTH (m)	OUTLET DEPTH (m)	TW DEPTH (m)	OUTLET VEL. (m/s)	TW VEL. (m/s)
0.00	57.20	0.00	-0.09	0-NF	0.00	0.00	0.00	0.00	0.00	0.00
0.63	57.57	0.31	0.37	3-M1t	0.30	0.21	0.35	0.35	0.86	0.47
1.26	57.79	0.50	0.59	3-M1t	0.48	0.33	0.52	0.52	1.15	0.59
1.89	57.97	0.65	0.77	3-M1t	0.63	0.44	0.66	0.66	1.37	0.68
2.52	58.12	0.80	0.92	3-M2t	0.78	0.53	0.77	0.77	1.55	0.74
3.15	58.26	0.94	1.06	3-M2t	0.91	0.61	0.86	0.86	1.74	0.81
3.78	58.38	1.07	1.18	3-M2t	1.05	0.69	0.94	0.94	1.91	0.87
4.20	58.46	1.16	1.26	3-M2t	1.20	0.74	0.99	0.99	2.01	0.90
5.04	58.62	1.34	1.42	3-M2t	1.20	0.84	1.08	1.08	2.22	0.96
5.67	58.71	1.47	1.51	3-M2t	1.20	0.91	1.09	1.09	2.48	0.97
6.30	58.89	1.61	1.69	3-M2t	1.20	0.97	1.09	1.09	2.76	0.97

El. inlet face invert	57.20 m	El. outlet invert	57.11 m
El. inlet throat invert	0.00 m	El. inlet crest	0.00 m

PRESS: <KEY> TO CONTINUE <W> FOR PROFILE TABLE
 <P> TO PLOT <I> FOR IMPROVED INLET TABLE

1- Help 2 3 4-Type 5-End 6 7 8 9-DOS 10

**HY8 PERFORMANCE CURVE PROMPT SCREEN
 2100 mm SPAN BY 1200 mm RISE CULVERT**

Figure 31-8K