

STORAGE CAPACITY, m ³ / SPACING, m															
Spillway Height	V-Ditch, 2:1 Fore, 2:1 Back Ditch Grade, up to:					V-Ditch, 3:1 Fore, 2:1 Back Ditch Grade, up to:					V-Ditch, 3:1 Fore, 3:1 Back Ditch Grade, up to:				
	2%	3%	4%	5%	6%	2%	3%	4%	5%	6%	2%	3%	4%	5%	6%
m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m	m ³ /m
0.60	11/20*	7/13*	5/10*	4/8*	4/6*	13/25*	9/16*	7/12*	5/10*	5/8*	16/30	11/20	8/15	6/12	5/10
0.75	21/38	14/26	11/19	8/15	7/13	26/48	18/32	13/24	11/19	9/16	32/58	21/38	16/29	13/23	11/19
0.90	36/66	24/44	18/33	15/27	12/22	46/83	30/55	23/41	18/33	15/28	55/100	36/66	27/50	22/40	18/33
1.05	58/105	39/70	29/53	23/42	19/35	72/132	48/88	36/66	29/53	24/44	87/158	58/106	43/80	35/63	29/52

** These spacings are for information only. Use the minimum spacing from Figure 37-3G instead.*

SEDIMENT TRAPS IN V-DITCHES

Figure 37-3E