



NO LOAD CAMBER AND REAMING DIAGRAM (mm)
(SKETCH SHOWN FOR CREST VERTICAL CURVE)

Span Length	Camber Tolerance at Quarter Points and Centerline of Splice					
	Centerline Bearing End Support	¼Point	½Point	Centerline Splice	¾Point	Centerline Bearing Interior Support
≥ 30 m	+ 0 mm	+ 14 mm	+ 19 mm	+ 13 mm	+ 14 mm	+ 3 mm
< 30 m	+ 0 mm	+ 7 mm	+ 10 mm	+ 6 mm	+ 7 mm	+ 3 mm

TABLE OF CAMBERS (mm)											
	CL BEARING BENT NO. 1	¼ POINT	½POINT	CL SPLICE "I"	¾POINT	CL BENT NO. 2	¾POINT	CL SPLICE "II"	½POINT	¼POINT	CL BEARING BENT NO. 3
DEAD LOAD - STEEL	0					0					0
DEAD LOAD - DECK	0					0					0
DEAD LOAD - RAILING	0					0					0
SUBTOTAL	0					0					0
VERTICAL CURVE	0					0					0
TOTAL CAMBER	0	A	B	C	D	0	E	F	G	H	0

BEAM CHAMBER

Figure 64-5A